

GARDiS Configuration Sheet

Everything you need to consider when setting up your GARDiS Access Control System

The Benefits GARDiS Web Embedded Access Control Units



Up to
5,000
Users



Up to
1,000+
Access
Groups



Up to
15,000
Event
Buffers



Up to
10
Wireless
Locks



Up to
10
Expanders
(44 Doors)

How Many Doors?

1-4 Doors
No Dongle
Required

5-10 Doors
GARDiS Web 10
5002-6010

11-20 Doors
GARDiS Web 20
5002-6020

21-44 Doors
GARDiS Web 44
5002-6044

Select Controller Unit



GARDiS
1 Door
5002-6001



GARDiS
2 Door
5002-6002



GARDiS
4 Door
5002-6004

Add an Extension



GARDiS
4 EXT
5002-6005



GARDiS
I/O EXT
5002-6006




Assa Abloy
Aperio AH30
2920-0555




Simons Voss
Smart Intego
2920-0556

Choose your Encryption Technology



- Sector
- CSN
- DESfire



Choose your Reader



GARDiS Mullion Reader

- 5002-0600 - Proximity
- 5002-0610 - MIFARE CSN
- 5002-0620 - MIFARE Sector
- 5002-0630 - DESfire
- Keypad Option Available




GARDiS Square Reader

- 5002-0602 - Proximity
- 5002-0612 - MIFARE CSN
- 5002-0622 - MIFARE Sector
- 5002-0632 - DESfire
- Keypad Option Available



GARDiS Bluetooth Low Energy

- 2920-0560 - Mullion
- 2920-0562 - Square



Panel Mount Reader

- 5002-0618 - Sector CSN
- 5002-0638 - DESFire/Sector



PANELgarde Reader

- 5002-0430 - Proximity



PC Enrolment Reader

- 5002-0449 - Prox/MIFARE
- 5002-0447 - TDSi Sector
- 5002-0448 - TDSi DESFire

Choose your Credentials

Proximity Cards

- 4262-0245 - Card W/Logo + ID
- 4262-0246 - Fobs

MIFARE

- 2920-3002 - 1K CSN Card
- 2920-3004 - 1K Sector Card
- 2920-6020 - 4K DESfire Card

Bluetooth Low Energy

- 2920-0570 - Bluetooth Credential

Notes
